

TECHNICAL DATA

# Fluke 700HTH-1 Hydraulic Test Hose



## Key features

- Hose and fittings connect directly to the Fluke 700HTP-1 test pressure port
- Includes plugs and caps to eliminate fluid loss in hose, eliminates the need to re-prime the hose
- Self-sealing fittings with easy finger tight connections
- Low volumetric expansion and a negligible pressure drop at rated pressures

## Product overview: Fluke 700HTH-1 Hydraulic Test Hose

The Fluke 700HTH-1 hydraulic test hose is a 10,000 psi, 690 bar working pressure test hose that features stainless steel and nylon construction for use in connecting a Fluke-700HTP-1 or other hydraulic test pump to a unit under test.

The Fluke 700HTH-1 allows connection to both a Fluke pressure module and a calibration unit under test from a Fluke 700HTP-1 hydraulic test pump simultaneously. 700HTH-1 is compatible with water and non-corrosive oil.

## Specifications: Fluke 700HTH-1 Hydraulic Test Hose

Mechanical and General Specifications	
Minimum bend radius	60 mm / 2.36 in.
Temperature	- 40°C to +120°C, ( -40°F to +250°F)
Material	Nylon, stainless steel, zinc, plated steel, and nitrile



Dimensions	.84 m (33 in) long without adapter fittings
Weight	412.8 g (.910 oz)
Warranty	One year

## Ordering information



### **Fluke 700HTH-1**

Hydraulic Test Hose

- 
- Hose with (2) 1/4" NPT female output connections
  - (2) adapters that to convert 1/4" NPT female to 1/4" NPT male (include sealing caps)
  - 1/4 in NPT female to 1/4 in BSP male adapter
  - Instruction sheet
-



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
06/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**