

KT203

Digital AC/DC Clamp Meter

PRODUCT DATA SHEET

KT203

DIGITAL AC/DC CLAMP METER

- Measures Current up to 400A AC/DC
- Measures Voltage up to 600V AC/DC
- Resistance
- Continuity buzzer
- 33mm jaw
- Sleep feature
- Data hold memory function
- Display: 4000 counts
- Complies to IEC61010-1 (CAT. III) UL3111 & VDE0411 300V



SPECIFICATIONS

AC CURRENT (A) AUTO-RANGING(50/60HZ)

| Range | Measuring Range | Accuracy |
|-------|-----------------|-------------------|
| 40A | 0-40.00A | ± 3.0% rdg ± 8dgt |
| 400A | 15.0-299.9A | ±3.5% rdg ±6dgt |
| | 300.0-400.0A | ±4.0% rdg ±6dgt |

DC CURRENT (A) AUTO-RANGING

| Range | Measuring Range | Accuracy |
|-------|-----------------|-------------------|
| 40A | 0-40.00A | ± 3.0% rdg ± 8dgt |
| 400A | 15.0-299.9A | ±3.5% rdg ±6dgt |
| | 300.0-400.0A | ±4.0% rdg ±6dgt |

AC VOLTAGE (V) AUTO-RANGING(50/60HZ)

| Range | Measuring Range | Accuracy |
|-------|-----------------|-----------------|
| 400V | 0-400.0V | ±2.0% rdg ±5dgt |
| 600V | 15.0-299.9A | |

DC VOLTAGE (V) AUTO-RANGING

| Range | Measuring Range | Accuracy |
|-------|-----------------|-----------------|
| 400V | 0-400.0V | ±1.5% rdg ±5dgt |
| 600V | 150-600V | |

RESISTANCE (Ω/CONTINUITY) AUTO-RANGING (BUZZER BEEPS BELOW 50±35 Ω)

| Range | Measuring Range | Accuracy |
|-------|-----------------|-----------------|
| 400Ω | 0-400 Ω | ±2.0% rdg ±5dgt |
| 4000Ω | 150-4000 Ω | |

| | |
|--------------|-----------|
| Reading Type | Averaging |
|--------------|-----------|

ACCESSORIES

- Test leads
- Batteries
- Instruction Manual

OPTIONAL

- Calibration Certificate