

OMICRON



CMLIB REF6xx

Technical Data





© OMICRON electronics GmbH 2015. All rights reserved.

This technical data was extracted from the following manual: CMLIB REF6xx.AE.1


All rights including translation reserved. Reproduction of any kind, for example, photocopying, microfilming, optical character recognition and/or storage in electronic data processing systems, requires the explicit consent of OMICRON.

The document content represents the technical status at the time of writing and is subject to change without prior notice.

We have done our best to ensure that the information given in this document is useful, accurate and entirely reliable. However, OMICRON does not assume responsibility for any inaccuracies which may be present.

OMICRON electronics translates this document from the source language English into a number of other languages. Any translation of this document is done for local requirements, and in the event of a dispute between the English and a non-English version, the English version of this document shall govern.

Technical Data

Accuracy of set <i>CMLIB REF6xx</i> plus CMC		
Guaranteed	Error < 0.07 % of reading + 700 μ V	
Typical	Error < 0.035 % of reading + 350 μ V	
DC offset		
Guaranteed	< 1.6 mV	
Typical	< 250 μ V	
Environmental conditions		
Operating temp.	0 ... 50 °C (32 ... 122 °F).	
Storage temp.	-25 ... 70 °C (-13 ... 158 °F).	
Humidity	5 ... 95 % relative humidity, no condensation.	
EMC and Safety Standards		
EMC	The product adheres to the electromagnetic compatibility (EMC) Directive 2004/108/EC (CE conform).	
- Emission	Europa: EN 61326-1 International: IEC 61326-1 USA: FCC SubpartB of part 15 Class A	
- Immunity	Europa: EN 61326-1 International: IEC 61326-1	
Safety	The product adheres to the low voltage Directive 2006/95/EC (CE conform). Europa: EN 61010-1 International: IEC 61010-1 USA: UL 61010-1 Canada: CAN/CSA-C22.2 No 61010-1-04	
Safety Standard	Manufactured in an ISO9001-certified quality management system.	

