

TXL830, TXL850 and TXL870

Extra load units for TOR KEL test system



- Provide higher load currents for concurrent power tests
- Discharging process controlled by a TOR KEL unit
- Connect directly to the battery under test

DESCRIPTION

TXL

These resistive extra loads do not perform any regulating functions.

They are designed for use together with TOR KEL battery load units. Their purpose is to provide higher load currents for use in constant current or constant power tests. Together, TOR KEL and the TXL extra loads form a system that can discharge batteries with currents of up to several kA. TXL extra loads are connected directly to the battery, and TOR KEL measures the total current using a clamp-on ammeter.

TXL extra loads are shut down automatically when TOR KEL is stopped.

TOR KEL / TXL - systems examples

Max. constant current (A)	Number of TOR KEL-units	Number of TXL-units
TOR KEL 820 + TXL830, 12 V battery (6 cells)¹⁾		
234	1	1
571	1	4
918	1	6
TOR KEL 820 + TXL830, 24 V battery (12 cells)¹⁾		
495	1	1
1170	1	4
1890	2	6
TOR KEL 820 + TXL850, 48 V battery (24 cells)¹⁾		
499	1	1
1189	1	4
1918	2	6


¹⁾ Discharge from 2.15 V to 1.8 V per cell

Max. constant current (A)	Number of TOR KEL-units	Number of TXL-units
TOR KEL 840/860 + TXL830, 24 V battery (12 cells)¹⁾		
263	1	1
670	2	2
1005	3	3
TOR KEL 840/860 + TXL850, 48 V battery (24 cells)¹⁾		
264	1	1
909	2	3
TOR KEL 840/860 + TXL870, 110 V battery (54 cells)¹⁾		
188	1	1
532	2	4
845	2	8
TOR KEL 840/860 + TXL870, 120 V battery (60 cells)²⁾		
194	1	1
557	2	4
895	2	8
TOR KEL 840/860 + TXL870, 220 V battery (108 cells)¹⁾		
94	1	1
266	2	4
423	2	8

¹⁾ Discharge from 2.15 V to 1.8 V per cell

²⁾ Discharge from 2.15 to 1.75 V per cell

APPLICATIONS



TOR KEL and the extra load TXL

SPECIFICATIONS

Specifications are valid at nominal input voltage and an ambient temperature of +25°C, (77°F). Specifications are subject to change without notice.

Environment

Application field The instrument is intended for use in high-voltage substations and industrial environments.

Temperature Operating
0°C to +40°C

Storage & transport
-40°C to +70°C

Humidity
5% – 95% RH, non-condensing

CE-marking

LVD 2006/95/EC
EMC 2004/108/EC

General

Mains voltage

100 – 240 V AC, 50 / 60 Hz

Power consumption

75 W (max)

Protection

Thermal cut-outs, automatic overload protection

Dimensions

Instrument 210 x 353 x 600 mm

Transport case 265 x 460 x 750 mm

Weight 13 kg

21.4 kg with transport case

Cable sets

for TXL830 and TXL 850 2 x 3 m, 70 mm², 270 A, with cable lug. Max. 100 V. 5 kg

for TXL870 2 x 3 m, 25 mm², 110 A, with cable lug. Max. 480 V. 3 kg

Load Section

	TXL830	TXL850	TXL870
Max. voltage d.c.	28 V	56 V	140 V / 280 V
Max. current	300 A	300 A	112 A at 140 V 56 A at 280 V
Max. power	8.3 kW	16.4 kW	15.8 kW
Internal resistance, 3-position selector			
Position 1	0.275 Ω	0.55 Ω	4.95 Ω
Current 100 A	at 27.6 V (12 x 2.3 V)	at 55.2 V (24 x 2.3 V)	-
78.5 A	at 21.6 V (12 x 1.8 V)	at 43.2 V (24 x 1.8 V)	-
50.1 A	-	-	at 248.4 V (108 x 2.3 V)
39.2 A	-	-	at 194.4 V (108 x 1.8 V)
Position 2	0.138 Ω	0.275 Ω	2.48 Ω
Current 200 A	at 27.6 V	at 55.2 V (24 x 2.3 V)	-
156 A	at 21.6 V	43.2 V (24 x 1.8 V)	-
Position 3	0.092 Ω	0.184 Ω	1.24 Ω
Current 300 A	at 27.6 V	at 55.2 V (24 x 2.3 V)	-
235 A	at 21.6 V	43.2 V (24 x 1.8 V)	-
100 A	-	-	at 124.2 V (54 x 2.3 V)
78.4 A	-	-	at 97.2 V (54 x 1.8 V)

Ordering information	
Item	Part number
Extra loads for use with TOR KEL systems	
TXL830	BS-59093
TXL850	BS-59095
TXL870	BS-59097
Cable sets	
For TXL830 and TXL 850	
2 x 3 m, 70 mm ² , 270 A, with cable lug. Max. 100 V. 5 kg	GA-00554
For TXL870	
2 x 3 m, 25 mm ² , 110 A, with cable lug. Max. 480 V. 3 kg	GA-00552

UK

Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES

4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES

Valley Forge USA, College Station USA, Sydney
AUSTRALIA, Täby SWEDEN, Ontario CANADA,
Trappes FRANCE, Oberursel GERMANY, Aargau
SWITZERLAND, Kingdom of SAUDI ARABIA, Mumbai
INDIA, Johannesburg SOUTH AFRICA, Chonburi
THAILAND

CERTIFICATION ISO

Registered to ISO 9001:2008 Cert. no. Q 09250
Registered to ISO 14001:2004 Cert. no. EMS 61597

TXL820_TXL850_TXL870_SS_EN_V0
1

www.megger.com